

**GLT**  
PRODUCTS


# Vinaflex™

Noise Reduction Materials



# Vinaflex™ Noise Barrier

## Non-reinforced Rolls (VN)



### Vinaflex Noise Barrier (VN)

GLT Products' Vinaflex (VN) Noise Barrier is a flexible, non-reinforced mass loaded vinyl that resists the passage of sound waves and reduces the transmission of airborne noise. Vinaflex (VN) is ideal for direct application to the noise source and/or to the housing covering the noise source.

Vinaflex (VN) Noise Barrier won't shrink, rot or cause metal corrosion and also features a strong resistance to adverse environmental conditions, oils, weak acids and alkalis. Vinaflex (VN) can be combined with acoustical foams, mineral fiber, glass fiber and ceramic fiber insulation to provide lightweight, efficient composites with high transmission losses over a broad frequency range.

Vinaflex (VN) Noise Barrier is offered in the following sizes:

#### Standard Roll Size By Density:

	Density	Roll Size	
VN-50	(1/2 lb./sq. ft.)	48" x 50'	* Custom roll lengths available upon request
VN-100	(1 lb./sq. ft.)	48" x 50'	
VN-100	(1 lb./sq. ft.)	54" x 60'	
VN-150	(1-1/2 lb./sq. ft.)	48" x 25'	
VN-200	(2 lb./sq. ft.)	48" x 25'	

In addition, the reduction of airborne noise and the high density properties exhibited by Vinaflex (VN) are attained without the use of hazardous lead or heavy metals.

Basic installation instructions are available upon request.

#### Acoustical Properties\*

Vinaflex (VN) Noise Barrier provides the following noise reduction.

Noise transmission Loss (dB)/Frequency (Hz)

Hz	125	250	500	1000	2000	4000	STC
db reduction by density:							
VN-50	8	13	17	22	27	31	20
VN-100	16	17	22	27	31	36	26
VN-150	17	19	25	31	36	44	29
VN-200	16	22	26	32	35	40	31

\*per ASTM E-90-97  
E413-87

#### Typical Physical Properties for VN-100\*

Weight	1 lb./sq. ft.
Tensile Strength	2,750 KPa (400 psi)
Tear Strength	12.5 Kg/cm (70 lbs./in.)
Thickness	.100"
Ultimate Elongation	200%
Flammability	SE "0" in/min.
Temperature Range	-40°F to 180°F

**\*Note: The physical and acoustical properties shown for Vinaflex non-reinforced rolls (VN) are applicable for the other types of Vinaflex included in this brochure.**

## Vinaflex™ Noise Barrier

### Reinforced Rolls (RR)

#### Vinaflex Reinforced Rolls (RR)

GLT Products Vinaflex (RR) Noise Barrier is a flexible, reinforced mass loaded vinyl that resists the passage of sound waves and reduces the transmission of airborne noise. Vinaflex (RR) is used as a free hanging acoustical curtain panel, typically with grommets and loop fasteners.


Vinaflex (RR) utilizes a high strength poly fabric in combination with mass loaded vinyl to dramatically improve its durability, tear and hanging strength.

Vinaflex (RR) Noise Barrier won't shrink, rot or cause metal corrosion and also features a strong resistance to adverse environmental conditions and UV light. Vinaflex (RR) can be combined with a quilted fiberglass decoupler to improve acoustical performance.

Vinaflex (RR) Noise Barrier is offered in the following sizes:

#### Standard Roll Size By Density:

	Density	Roll Size
<b>RR-50</b>	(1/2 lb./sq. ft.)	48" x 50'
<b>RR-100</b>	(1 lb./sq. ft.)	48" x 50'



## Vinaflex™ Noise Barrier

### Vinaflex Rolls with Foil Facing (FF)

#### Vinaflex Rolls with Foil Facing (FF)


GLT Products Vinaflex (FF) Noise Barrier is a flexible, mass loaded vinyl barrier faced with a scrim reinforced aluminum foil on one side. Vinaflex (FF) is used for wrapping noisy pipes, ducts and valves in a wide variety of applications.

Vinaflex (FF) may be combined with a quilted fiberglass decoupler to improve acoustical performance, thermal conductivity and lower installation costs. The durable reinforced foil facing serves as a protective jacket and readily accepts matching lag tape.

Vinaflex (FF) Noise Barrier is offered in the following sizes:

#### Standard Roll Size By Density:

	Density	Roll Size
<b>FF-50</b>	(1/2 lb./sq. ft.)	48" x 50'
<b>FF-100</b>	(1 lb./sq. ft.)	48" x 50'
<b>FF-100</b>	(1 lb./sq. ft.)	54" x 30'



## Vinaflex™ Noise Barrier

Vinaflex with Acoustic Foam Laminate (FB)

### Vinaflex with Foam (FB)

GLT Products Vinaflex (FB) Noise Barrier is a flexible, non-reinforced mass loaded vinyl combined with a 1/4", 1/2" or 1" open-cell urethane and other foams. The open-cell design of the foam readily accepts and dissipates sound waves, insuring maximum acoustical absorption. This foam facing also acts as a decoupler, breaking and separating vibrations between the two materials. Vinaflex (FB) Noise Barrier won't shrink, rot or cause metal corrosion and also features a strong resistance to adverse environmental conditions.



Vinaflex (FB) Noise Barrier provides the following, when applied directly to solid objects:

- 1) Sound vibration isolation in the barrier (sound/vibration decoupler).
- 2) Easier gluing/adhering.

Vinaflex (FB) Noise Barrier is offered in the following sizes:

### Standard Roll Size By Density:


	Density	Roll Size
<b>FB-50</b>	(1/2 lb./sq. ft.)	54" x 25'
<b>FB-100</b>	(1 lb./sq. ft.)	54" x 25'

## Vinaflex™ Noise Barrier

Vinaflex with Fiberglass Absorber/Decoupler (VP)

### Vinaflex with Absorber / Decoupler (VP)

GLT Products Vinaflex (VP) Noise Barrier is a flexible, mass loaded vinyl laminated to a quilted fiberglass decoupler on one or both sides. The combination forms a thin, light-weight acoustical product that displays excellent mechanical properties, while providing superior sound transmission loss. Sound waves originating from the source will be initially absorbed by the fiberglass and then blocked by the mass loaded vinyl. Any reflected sound wave component will be further dissipated into the fiberglass absorber.



Vinaflex (VP) Noise Barrier is offered in the following sizes:

Note:


VP1 = 1" quilted fiberglass

VP2 = 2" quilted fiberglass

Vinaflex (VP) is also available with an added outer finish of scrim reinforced foil on one side.

### Standard Roll Size By Density:

	Density	Roll Size
<b>VP1-50</b>	(1/2 lb./sq. ft.)	54" x 30'
<b>VP1-100</b>	(1 lb./sq. ft.)	54" x 30'
<b>VP2-50</b>	(1/2 lb./sq. ft.)	54" x 30'
<b>VP2-100</b>	(1 lb./sq. ft.)	54" x 30'



GLT Products offers a complete line of Vinaflex Noise Barriers to meet the physical and performance requirements of virtually any acoustical application. The primary component of the Vinaflex line is a flexible, mass loaded vinyl barrier that is specifically engineered for efficient sound isolation.

When combined with mineral fiber, acoustical foam, glass fiber, or ceramic fiber, Vinaflex barrier materials form economical high performance composites that provide high transmission loss over a broad frequency range.

Vinaflex Noise Barrier is offered in the following forms:

### **Vinaflex with Absorber / Decoupler (VP)**

Vinaflex VP consists of a flexible, mass loaded vinyl barrier laminated to a quilted fiberglass decoupler on one or both sides. This series features the highest STC (Standard Transmission Class) rating and, per ASTM-E84, meets a Class A fire rating.




### **Vinaflex Standard Rolls (VN)**

Vinaflex VN is a non-reinforced mass loaded vinyl noise barrier that is ideal for direct application to piping, ductwork, and equipment, as well as the housing covering the noise source.

### **Vinaflex with Foam (FB)**

Vinaflex FB consists of a flexible, mass loaded vinyl barrier combined with open-cell urethane foam. The textured surface of the foam combines high acoustical absorption with economical cost. The foam's high performance and durability properties make it ideal for a multitude of OEM applications.

### **Vinaflex FB with Foil Facing (VF)**



### **Vinaflex Reinforced Rolls (RR)**

Vinaflex RR is a flexible, mass loaded vinyl with a high strength polyester fabric, which improves the material's durability and strength. Vinaflex (RR) is typically used as a free hanging acoustical curtain panel or partition for in-plant noise control.

### **Vinaflex Aluminum (AF) and Stainless Steel (SF) Facings**

Vinaflex AF and SF metal noise barriers consist of a mass loaded vinyl which is machine laminated to a continuous roll of aluminum or stainless steel jacketing.

Type AF and SF are used in combination with mineral fiber, glass fiber, or ceramic fiber as a path control form of acoustic treatment.



### **Vinaflex Foil / Scrim Faced Rolls (FF)**

Vinaflex FF consists of a flexible, mass loaded vinyl barrier faced with a scrim reinforced aluminum foil. This series is an economical, effective treatment for noisy pipes, ducts and valves. The foil facing readily accepts matching lag tape.



# Vinaflex™ Noise Barrier

## Aluminum (AF) and Stainless Steel (SF) Sheets and Rolls

### Aluminum (AF) and Stainless Steel (SF) Sheets and Rolls

Vinaflex Noise Barrier (AF) and (SF)

GLT Products Vinaflex Metal Noise Barrier is a mass loaded vinyl which is machine laminated to a continuous roll jacketing of aluminum (Type AF) or stainless steel (Type SF).

Vinaflex (Type AF) and (Type SF) Noise Barriers are used in combination with mineral fiber, glass or ceramic fiber insulation as a path control form of acoustic treatment.

Vinaflex (Type AF) and (Type SF) Noise Barriers are ideal for isolating piping and ductwork within exposed commercial and industrial areas as well as exterior areas requiring weather resistance.

Vinaflex (Type AF) and (Type SF) Noise Barriers are offered in the following combinations and sizes:

Density                      Roll Size                      Metal Thickness

AF-50	36" x 33 1/2'	.010", .016"
AF-100		
AF-200		
SF-50	36" x 33 1/2'	.010", .016" & .020"
SF-100		
SF-200		

Vinaflex (Type AF) and (Type SF) are also available in cut to size 36" wide sheets.



### Acoustical Properties\*

Vinaflex Type AF-100 and Type SF-100 Noise Barriers provide the following noise reduction.

Noise Transmission Loss (dB)/Frequency (Hz)

Hz	125	250	500	1000	2000	4000	STC
dB	20	21	23	29	34	40	29

\*Per ASTM E-90

©2010



**Great Lakes Textiles, Inc.**

6810 Cochran Road

Solon, Ohio 44139

1-800-874-1748 • Fax: 1-440-914-1133

[www.gltproducts.com](http://www.gltproducts.com)

[info@gltproducts.com](mailto:info@gltproducts.com)

Member of

