



(800)874-1748
(440)914-1122
Fax: (440)914-1133

6810 Cochran Road · Solon, Ohio 44139

www.gltproducts.com

ROLL ON CORNERBEAD DATA SHEET

Description:

This product is a combination of metal and paper wallboard cornerbead tape that is used in conjunction with Gold Bond joint compound to conceal inside and outside corners of ductwork insulation.

REQUIRED CHARACTERISTICS

General:

This product shall consist of 2 parallel metal strips bonded 100% to unperforated, unsparked paper tape with moisture and alkali resistant adhesive. The 2 metal strips shall be centered such that a center space of $0.045'' \pm .005''$ exists between the 2 metal strips and positioned so that the 2 metal strips are equal distance from each edge of the paper.

Material Metal:

2 pcs. – Steel 1/2" width X .012" thickness. The metal shall be electrogalvanized, half hard, Rockwell test 70-85, clean, neutral surface to allow adhesion on both sides.

Paper Tape:

Paper backing shall be 2-1/8" wide wallboard tape.

Adhesive:

The adhesive used to bond the two steel trips to the unperforated, unsparked paper tape shall not be affected by the joint compound used to adhere the tape to a drywall joint. The adhesive shall not be affected by temperature, humidity or corrosion when the multi-flex cornerbead tape is stored before it is used.

The adhesive (latex type waterproof NT-565 adhesive) shall be applied on each metal strip to within 1/32" of the edges, which under pressure, is forced to the outer edges of the metal, creating total lamination of each metal strip to the paper.