

Two Component Polyurethane Foam Systems are portable, self-contained dispensing systems. When used according to the manufacturer's instructions, they supply thermal insulation and sound attenuation. These spray foams are permanent and dry within minutes of application and are ideal for repairs, renovations, new installations and production applications. The 12 oz. can is a one-component system.

- Solvent Free, self cleaning
- dispenser gun
- Contains no urea formaldehyde
- High R-value
- Convenient sized
- Class 1 availability
- Closed cell
- Sets up in 45 seconds
- Cures in 5 minutes
- Factory pressurized, requires no outside power source
- Operating temperatures -250° F to +250° F



	DENSITY(PCF)	YIELD	CONTENTS
U2-200 KIT:	1.75	200 Board Feet 16.6 Cubic Feet	2-Component Foam, P2 Application Gun, Color-Coded 10 feet Hoses (pre-connected), Extra Spray Nozzles, Wrench, Latex Gloves, O-ring, Lubricant
U2-600 KIT:	1.75	600 Board Feet 50 Cubic Feet	Kits include A & B cylinders, P2 applicator gun with 10 ft hoses, extra spray nozzles, assembly wrench, latex gloves, lubricant
FOAM KIT 15:	1.75	15 Board Feet	2-Component Polyurethane Foam, Applicator, 15 Ft Hoses
12 OZ. CAN		Yield depends on bead diameter	one-component polyurethane foam spray can