



(800)874-1748
(440)439-1300
Fax: (440)439-7236

6810 Cochran Road · Solon, Ohio 44139

www.gltproducts.com

TEFLON IMPREGNATED FIBERGLASS CLOTH STYLE 650

Style 650 is a PTFE impregnated fiberglass fabric engineered for the harsh environments found in many industrial facilities including acid plants, paper mills, and petrochemical plants. Designed for standard duty, this abrasion resistant jacketing has proven very durable in removable insulation pad service. Style 650 sews easily and has excellent non-flammability properties.

Property Data

Weight	17.0 oz/sq yd nominal
Thickness	0.016 in nominal
Width	60 in nominal
Tensile Strength	410 lb/in avg warp 375 lb/in avg fill
Materials	Woven fiberglass and PTFE resins
Color	Gray
Upper Use Temperature	550°F
Trapezoidal Tear Strength	20 lbs avg warp 20 lbs avg fill
Non-flammability – V-O rating; UL 94, Vertical Burning Test	

Important Properties

Oil resistant
Water resistant
High temp. resistant
Easily fabricated
Abrasion resistant
Rugged construction

Applications

Equipment covers
Splash shields
Expansion joints
Flange and valve covers
Safety clothing

All statements herein are expressions of opinion, which we believe to be accurate and reliable, but are presented without guarantee or responsibility on our part. Anyone intending to use recommendations contained in this publication concerning equipment, processing techniques or products should first satisfy himself that the recommendations are suitable for his use and meet all appropriate safety and health standards.