DATA SHEET

Mass Loaded Vinyl (MLV) is offered by GLT Products under the Vinaflex® brand name. Vinaflex® (FF) Noise Barrier is a flexible, mass loaded vinyl barrier faced with a scrim reinforced foil on one side. Vinaflex® (FF) is used for wrapping noisy pipes, ducts and valves in a wide array of industrial and commercial applications.

Vinaflex® (FF) may be combined with a quilted fiberglass decoupler to improve acoustical performance, thermal conductivity and lower installation costs. The durable reinforced foil facing serves as a protective jacket and readily accepts matching lag tape.



Specification and technical Information:						
Product	Weight	Roll Sizes				
FF-100	1 lb./ sq. ft.	48" x 50' and 54" x 30'				
FF-200	2 lb./ sq. ft.	48" x 25'				

Fire Rating: Class A per ASTM E-84 for FF-100 only.

Acoustical Properties/ Transmission Lost									
Freq.	Hz	125	250	500	1000	2000	4000	STC	
1# TL	dB	11	15	21	27	33	39	26	
2# TL	dB	19	23	27	32	37	42	32	

TS1202REV10.III

For more information on GLT Products, please call toll-free at 800.874.1748 or visit us online at www.gltproducts.com.



HEADQUARTERS:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

DISTRIBUTION CENTERS:

Ohio: 6810 Cochran Road | Solon OH 44139 | 440.914.1122

Texas: 2902 East 13th Street, Suite 200 | La Porte, TX 77571 | 713-670-9700

 North Carolina:
 109 Sands Road | Reidsville, NC 27320 | 1.800.551.9760

 California:
 4113 Gold River Lane | Stockton, CA 95215 | 1.800.833.4500