SUPERSEDES:

03-06-2003

MATERIAL SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION

REVISION DATE: 11-09-2007

Specialty Construction Brands, Inc.

An H.B. Fuller Company

1105 S. Frontenac Street

Aurora, IL 60504

Phone: 1-800-323-7407

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT IDENTIFIER: 802250PM
PRODUCT NUMBER: FD3007
PRODUCT NAME: FOSTER 30-07
PRODUCT DESCRIPTION: Coating

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS#	PERCENT	OSHA PEL
Calcium carbonate	471-34-1	10 - 30	TWA (Total dust) 15MG/M3 TWA (Respirable dust) 5MG/M3
No_Common_Name_Found:CAS:617 88-76-9	61788-76-9	10 - 30	
Chlorinated paraffin	63449-39-8	10 - 30	Not established
Kaolin clay	1332-58-7	5 - 10	TWA (Total dust) 10MG/M3 TWA (Respirable dust) 5MG/M3
Ethyl alcohol	64-17-5	1 - 5	TWA 1000ppm

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Causes skin irritation.

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment

recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. No hazard in normal industrial use.

LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Lungs Blood Liver Central nervous system

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease; Blood disorders (like anemia); Liver disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 200C (392F) TCC
AUTOIGNITION TEMPERATURE: Not established
LOWER EXPLOSIVE LIMIT (% in air): Not established
UPPER EXPLOSIVE LIMIT (% in air): Not established

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS: There is a possibility of pressure buildup in closed containers

when heated. Water spray may be used to cool the containers.

Material will burn in a fire.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide Chlorine containing gases

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this

MSDS. Additional precautions may be necessary based on special

circumstances created by the spill including; the material spilled, the quantity

of the spill, the area in which the spill occurred.

CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers

for disposal. Keep spilled product out of sewers, watersheds, or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in

a well ventilated area.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is

not available or sufficient to eliminate symptoms.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL
Calcium carbonate	TWA 10MG/M3	Not established
No_Common_Name_Found:CAS: 61788-76-9		
Chlorinated paraffin	Not established	Not established
Kaolin clay	TWA (Respirable dust) 2MG/M3	Not established
Ethyl alcohol	TWA 1000ppm	Not established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid COLOR: Red

ODOR: Mild Solvent
ODOR THRESHOLD: Not established

WEIGHT PER GALLON (lbs.): 10.4

SPECIFIC GRAVITY: 1.25 SOLIDS (% by weight): 50.0

pH: Not established BOILING POINT (deg. C): Not established FREEZING/MELTING POINT (deg. C): Not established VAPOR PRESSURE (mm Hg): Not established VAPOR DENSITY: Not established EVAPORATION RATE: Not established OCTANOL/WATER COEFFICIENT: Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Chlorine

containing gases

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50
Calcium carbonate	Oral LD50 Rat = 6450mg/kg
No_Common_Name_Found:CAS:61788-	
76-9	
Chlorinated paraffin	Oral LD50 Rat > 21500ml/kg
	Dermal LD50 Rabbit > 10ml/kg
Kaolin clay	Not established
Ethyl alcohol	Oral LD50 Rat = 1501mg/kg
	Inhalation LC50 Rat = 124.7mg/l

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: NOT REGULATED IATA: NOT REGULATED

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: This product is in compliance with the Canadian Domestic Substance List

requirements.

EUROPEAN EINECS: This product is in compliance with the European Inventory of Notified and

Existing Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name CAS# %

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2B

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Specialty Construction Brands, Inc. from its suppliers, and because Specialty Construction Brands, Inc. has no control over the conditions of handling and use, Specialty Construction Brands, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Specialty Construction Brands, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Specialty Construction Brands, Inc. products to comply with all applicable federal, state and local laws and regulations.