

SAFETY DATA SHEET

REVISION DATE: 10-10-2014 SUPERSEDES: 03-21-2013

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: FOSTER 85-20
PRODUCT DESCRIPTION: Adhesive
INTENDED USE: Adhesive
PRODUCT IDENTIFIER: 802414PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:





GHS Signal Word: Danger

GHS Classification: Skin Sensitisation Category 1; Germ Cell Mutagenicity Category 1B; Carcinogenicity

Category 1B; Reproductive Toxicity Category 2; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2; Hazardous to the aquatic environment - Acute Category 3; Hazardous to the aquatic environment - Chronic

Category 3

GHS Hazard Phrases: May cause an allergic skin reaction.; May cause genetic defects..; May cause cancer.;

Suspected of damaging fertility or the unborn child.; May cause damage to organs through prolonged or repeated exposure.; Harmful to aquatic life.; Harmful to aquatic

life with long lasting effects.

GHS Precautions:

Safety Precautions: Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective

equipment as required.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get

medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulation for hazardous wastes.



Print Date: 04-08-2015

FOSTER 85-20 802414PM

SAFETY DATA SHEET

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	Classification	Note
Methylene chloride	75-09-2	50 - 70	Carc. 2; H351	
Toluene	108-88-3	1 - 5	Asp. Tox. 1; H304 Acute Tox. 4; H302 Flam. Liq. 2; H225 Repr. 2; H361 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H336	
Rosin, pentaerythritol ester	8050-26-8	1 - 5	Aquatic Chronic 4; H413 Eye Irrit. 2A; H319 Skin Sens. 1; H317	
Ethyl alcohol	64-17-5	1 - 5	Eye Irrit. 2; H319 Flam. Liq. 2; H225	
Titanium dioxide	13463-67-7	0.1 - 1	Carc. 2; H351	* (see below)
Stoddard solvent	8052-41-3	0.1 - 1	Asp. Tox. 1; H304 Carc. 1A; H350 Muta. 1B; H340	
Tri(nonylphenol)phosphite	26523-78-4	0.1 - 1	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317	

^{*}This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Keep warm and quiet. Call a physician. IF SWALLOWED: Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

UNUSUAL FIRE AND EXPLOSION HAZARDS:

SPECIAL FIRE FIGHTING INSTRUCTIONS:

HAZARDOUS COMBUSTION PRODUCTS:

Use water spray, foam, dry chemical or carbon dioxide.

There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers. Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Carbon dioxide, Carbon monoxide Chlorine containing gases



Print Date: 04-08-2015

FOSTER 85-20 802414PM

SAFETY DATA SHEET

SECTION 6: ACCIDENTAL RELEASE MEASURES

Exposure to the spilled material may be irritating or harmful. Follow SPECIAL PROTECTION:

> personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the

quantity of the spill, the area in which the spill occurred.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

> area. Avoid breathing vapors. Use only with adequate ventilation.

Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

Keep container closed.

Emptied container retains vapor and product residue. Observe all labeled safeguards until container is cleaned. DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Aluminum is not an acceptable material of construction for pumps, mixers, fittings

or storage for this product.

Storage: Store in a cool, dry place.

EXPOSURE LIMITS:

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Note ACGIH EXPOSURE LIMITS OSHA PEL **Chemical Name** Methylene chloride 50 ppm TWA 25 ppm TWA 125 ppm STEL (see 29 CFR 1910.1052) Calcium carbonate * (see No data available. 15 mg/m3 TWA (total dust); 5 mg/m3 TWA below) (respirable fraction) Toluene 200 ppm TWA 20 ppm TWA 300 ppm Ceiling No data available. 1000 ppm TWA; 1900 mg/m3 TWA Ethyl alcohol 1000 ppm STEL Titanium dioxide * (see 10 mg/m3 TWA 15 mg/m3 TWA (total dust) below) Stoddard solvent 100 ppm TWA 500 ppm TWA; 2900 mg/m3 TWA Methyl alcohol 200 ppm TWA 200 ppm TWA; 260 mg/m3 TWA 250 ppm STEL

Skin absorption may potentially contribute to the overall exposure to this material.



FOSTER 85-20
Print Date: 04-08-2015
802414PM

SAFETY DATA SHEET

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

ENGINEERING CONTROL METHODS:

VENTILATION: Local exhaust ventilation or other engineering controls are normally

required when handling or using this product to avoid overexposure.

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent

absorption so that the TLV is not invalidated.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection will be required when ventilation or other

engineering controls can not reduce the exposure to acceptable levels.

Use supplied-air respiratory equipment as required.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid
COLOR: Off-white
ODOR: Solvent
ODOR THRESHOLD: Not established

pH: Not established FREEZING/MELTING POINT (deg. C): Not established BOILING POINT (deg. C): Not established FLASH POINT: Non flammable EVAPORATION RATE: Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

WEIGHT PER GALLON (lbs.): 10.80 SPECIFIC GRAVITY: 1.290

SOLUBILITY: Not established OCTANOL/WATER COEFFICIENT: Not established AUTOIGNITION TEMPERATURE: Not established DECOMPOSITION TEMPERATURE: Not established VISCOSITY: No data available.

SOLIDS (% by weight): 43.0

VOC, weight percent 6.15

VOC, U.S. EPA Method 24, less water and exempt 162g/liter of material

solvents (theoretically determined)



Print Date: 04-08-2015

FOSTER 85-20 802414PM

SAFETY DATA SHEET

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Aluminum alloys HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Chlorine containing gases Carbon monoxide, carbon

dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50	
Methylene chloride	ORAL LD50 RAT > 2,000 MG/KG	
Calcium carbonate	ORAL LD50 RAT 6,450 MG/KG	
Toluene	ORAL LD50 RAT 636 MG/KG INHALATION LC50-4H RAT 13 MG/L DERMAL LD50 RABBIT 8,390.00 MG/KG	
Ethyl alcohol	INHALATION LC50-4H RAT 125 MG/L	

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Contains a material that is suspected of causing cancer.

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause drowsiness or dizziness.

Specific target organ toxicity-single exposure: No data available.

Target organs potentially affected by exposure: Heart Liver Central nervous system Reproductive system Blood

Lungs Kidneys Eyes

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Liver disease, Overexposure to methylene chloride may cause cardiac effects (including the elevation of carboxyhemoglobin levels) which may be significant in smokers or persons with anemia or heart disease and those exposed to carbon monoxide, Blood disorders (like anemia), Lung disease, Kidney disease, Eye disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available. PERSISTENCE: No data available. BIOACCUMULATION: No data available.



SAFETY DATA SHEET

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Methylene chloride	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 140.8 - 277.8 mg/L [flow-
	through]; 96 Hr LC50 Pimephales promelas: 262 - 855 mg/L [static]; 96 Hr LC50
	Lepomis macrochirus: 193 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 193 mg/L
	[flow-through]
	Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: 1532 - 1847 mg/L [Static]; 48
	Hr EC50 Daphnia magna: 190 mg/L
	Acute Toxicity (Algae): 96 Hr EC50 Pseudokirchneriella subcapitata: >500 mg/L; 72 Hr
	EC50 Pseudokirchneriella subcapitata: >500 mg/L
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Lepomis macrochirus: >300 mg/L [static]; 96 Hr
	LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus
	mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-
	through]; 96 Hr LC50 Pimephales promelas: >100 mg/L [static]
	Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established
Toluene	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 15.22 - 19.05 mg/L [flow-
	through] (1 day old); 96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50
	Oncorhynchus mykiss: 5.89 - 7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus
	mykiss: 14.1 - 17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-
	static]; 96 Hr LC50 Lepomis macrochirus: 11.0 - 15.0 mg/L [static]; 96 Hr LC50 Oryzias
	latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static]; 96 Hr
	LC50 Poecilia reticulata: 50.87 - 70.34 mg/L [static]
	Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static]; 48
	Hr EC50 Daphnia magna: 11.5 mg/L
	Acute Toxicity (Algae): 96 Hr EC50 Pseudokirchneriella subcapitata: >433 mg/L; 72 Hr
	EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static]
Ethyl alcohol	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L [static]; 96
	Hr LC50 Pimephales promelas: >100 mg/L [static]; 96 Hr LC50 Pimephales promelas:
	13400 - 15100 mg/L [flow-through]
	Acute Toxicity (Daphnia): 48 Hr LC50 Daphnia magna: 9268 - 14221 mg/L; 24 Hr
	EC50 Daphnia magna: 10800 mg/L; 48 Hr EC50 Daphnia magna: 2 mg/L [Static]
	Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

This product contains greater than 10% chlorinated solvent. Spent chlorinated solvents are considered hazardous waste; however, as a component of a mixture, chlorinated solvents do not meet the RCRA definition of hazardous waste under 40 CFR 261. Consult state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Methylene chloride Toluene Methanol

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT: UN1593, DICHLOROMETHANE MIXTURE, 6.1, III. IN CONTAINERS

1930 POUNDS OR MORE: UN1593, DICHLOROMETHANE MIXTURE,

6.1. III. RO

IATA: UN1593, DICHLOROMETHANE MIXTURE, 6.1, III. IN CONTAINERS

1930 POUNDS OR MORE: UN1593, DICHLOROMETHANE MIXTURE,

6.1, III, RQ

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt



SAFETY DATA SHEET

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of

Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg,request@hbfuller.com to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Dichloromethane	75-09-2	50 - 70
Toluene	108-88-3	1 - 5
Methanol	67-56-1	0.1 - 1

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A D2B

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Dichloromethane	(Carcinogen)	75-09-2	50 - 70
Titanium dioxide	(Carcinogen)	13463-67-7	0.1 - 1
ISOBUTYL METHYL KETONE	(Carcinogen)	108-10-1	0.01 - 0.1
Quartz	(Carcinogen)	14808-60-7	0.001 - 0.01
ethylbenzene	(Carcinogen)	100-41-4	0.001 - 0.01
Benzene	(Carcinogen)	71-43-2	0.001 - 0.01
Toluene	(Developmental toxin)	108-88-3	1 - 5
Methanol	(Developmental toxin)	67-56-1	0.1 - 1
Methyl isobutyl ketone	(Developmental toxin)	108-10-1	0.01 - 0.1
Benzene	(Developmental toxin)	71-43-2	0.001 - 0.01
Benzene, methyl-	(Female reproductive toxin)	108-88-3	1 - 5
Benzene	(Male reproductive toxin)	71-43-2	0.001 - 0.01

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.

SECTION 16: OTHER INFORMATION



SAFETY DATA SHEET

SDS VERSION DATE: 10-10-2014

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment

recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.