GLT Products manufactures its braided draw cords with customer requirements in mind. We use only first quality fiberglass.

Applications

- Draw cord for removable safety spray shield
- Draw cord for insulated flange or value covers

Benefits

- Excellent chemical resistance
- Very high operating temperatures
- Will not burn or support flame
- · Will not rot or support fungus
- Low stretch (less than 5%)
- Same material as most high-end jackets
- Many other braid constuctions available



Data	
Part Number:	GCTEFLONCORD
Material:	Round braided E-Glass Fiberglass
Coating:	PTFE
Diameter:	1/8"
Color:	Black
Operating Temperature:	550°F continuous
Tensile:	200 pounds minimum

In addition to draw cords, GLT Products manufactures individual coated yarn products for those companies seeking materials for high temperature, chemical resistant overbraids. Many other sizes of braided, PTFE coated fiberglass cord are available, ranging from .007 diameter flat or round. All values are typical and should not be used for writing specifications. Please consult GLT Products.

For more information on GLT Products, please call toll-free at 800.874.1748 or online at www.gltproducts.com.



HEADQUARTERS

6810 Cochran Road Solon OH 44139 440.914.1122 440.914.1133 Fax 800.874.1748

GREENSBORO

50 I W. Camel Street Greensboro NC 2740 I 800.551.9760

STOCKTON

4283 Pock Lane Stockton CA 95206 800.833.4500

HOUSTON

8905 Market Street Houston, TX 77029 800.874.1748

Revised 0911

www.gltproducts.com info@gltcos.com